

Base Part Number: 76140



2004 E-Z-GO 1200 REFRESHER 4 WHEEL GASOLINE

STANDARD EQUIPMENT: (4 Cycle)

Engine: 11.0 H.P. rated, 4 cycle, 350 cc twin cylinder, air-cooled

Valve train: Overhead valve, overhead cam.

Lubrication: Pressurized oil system, washable permanent filter.

Balancer: Internal counter rotating balance shaft.

Ignition: Solid state with crank trigger, electronic timing advance, and RPM limiter.

Carburetor: Fixed jet float bowl with remote pulse fuel pump.

Air Cleaner: Replaceable dry cartridge with remote air intake.

Electrical System: External starter/generator, 12-volt maintenance free battery, 360 CCA, 51 minute reserve.

Drive Train: Automatic, continuously variable transmission (CVT) forward and reverse.

Transaxle: High efficiency differential with helical gears, 13.32:1 ratio, ground speed governor.

Brakes: Dual rear wheel mechanical drum brakes, self-adjusting with non-asbestos linings. Automatic park brake release with self-compensating system.

Front Suspension: Leaf springs with hydraulic shock absorbers.

Rear Suspension: Leaf springs with hydraulic shock absorbers with sway bar.

Steering: Self-compensating single reduction rack and pinion.

Fuel System: 6.0-gallon tank with mechanical fuel gauge gas cap.

Speed: Automatically governed to 10 - 11 MPH on level ground.

DIMENSIONAL SPECIFICATIONS:

Weight: 1,054 lbs. dry (fuel capacity 31 lbs.)

Length: 114.0 inches

Width: 48 inches at server (53 inches at top)

Height: 45.5 inches (at steering wheel)

Floor Height: 10 inches

Ground Clearance: 4.3 inches (at differential)

Seat Height: 26 inches

Wheel Base: 77 inches

Front Wheel Tread: 33.5 inches

Rear Wheel Tread: 38 inches

Turning Clearance Diameter: 21 feet

Tires: 18 x 8.50 x 8 (4 ply rated) - Front; 18 X 9.50 X 8 (6 ply rated) - Rear

Load Capacity: 1,200 lbs. (including operator, passenger, and loaded server unit). See sheet 2 for server capacity.

Seating: Vacuum formed fabric backed vinyl covers over thick cushion foam. Standard seating for operator and one passenger.

Intersecting Aisle Clearance: 83 inches

Turning Radius: 10.3 feet

FEATURES:

1. **Server Unit:** Allows service access to drive package.
2. **Chassis:** Welded high yield strength tubular steel.
3. **Body:** Front : Durashield™ of automotive quality injection molded TPE (thermoplastic elastomer).
Rear : Steel, replaceable lightweight panels.
4. **Finish:** Durashield™ powder primer and topcoat.
5. **Body Protection:** Flexible rear fenders and flexible front cowl . Wrap around front bumper.
6. **Safety:** Removable key switch, reverse warning indicator, "deadman" accelerator control, vinyl handgrip and hip restraints, manual F & R switch, and electric horn, rear view mirrors.
7. **Center Console:** Instrument panel with four drink holders.
8. **Steering Wheel:** Molded high impact plastic with dual handgrips, pencil holder, and a convenient clipboard.
9. **Windshield:** Polycarbonate
10. **Server Unit:**
 - Painted 5000 Series Aluminum construction.
 - Canvas Top with Aluminum Frame

Base Part Number: 76140

PAGE 2

CAPACITY of Server Units:

Display Area	6.6 SQ FEET
Beverage Service	3 each, 3.75 liter capacity Air pots
Canned Beverages (12 oz.)	12.5 cases
Cups	90 - 120 depending on size
Clean Ice	60 lbs
Max. weight Server Contents	500 lbs

SERVER UNIT ACCESSORIES

Sign Boards
Condiment Tray
Bottle Caddy
Mini Bottle Carrier
Humidor
Credit Card Machine Mount
Cash Drawer

VEHICLE OPTIONS:

Hub Caps:
 8" Chrome
 6" Moon Type
 Spoke - Silver & Black
 Spoke - Gold & Black
Hour Meter
Low Fuel Indicator Light
Low Oil Pressure Indicator Light
Non-Standard Paint
Ash Tray
Spark Arrester Muffler Kit
Individually Keyed
Optional seat colors
Tires:
 Turf Saver
 USA Trail
Headlights, Taillights, and Brake Lights
Turn Signals With 4 Way Flasher
Heavy Duty Battery

Specifications subject to change without notice.